



2177

get the moisture right

2178

baler moisture tester



www.farmscanag.com



- Operating Range (Moisture): 8% to 40% depending on baler type used
- Accurate throughout the normal range of stored hay
- Display Resolution: 0.1% moisture

BALE FASTER WITH ON-THE-GO MOISTURE READING

The 2177 mounts in the cab of the tractor and provides a direct readout for % moisture while baling hay.

Having the recommended moisture content during each step of the haymaking process is critical to finishing with a high quality product.

FEATURES

- Bale Type: Square bales and round bales
- Direct readout for % moisture while baling hay
- Average of readings updated and displayed every 3-5 seconds
- Backlit display for night use
- Built-in calibration button
- Above and below moisture limit indicator
- Sturdy display module mounting bracket with adjusting knobs
- Includes sensor kit, long-lasting sensor pad and stainless steel hardware

OPTIONS

- **2177C** 3.3m sensor extension cable
- **2177S** Spare bale chamber sensor

Due to the many variables associated with hay moisture measurements an occasional "spot check" using a handheld probe on finished bales is recommended.

MULTI SENSOR ON-THE-GO MOISTURE READING

The new 2178 with multi-sensor technology takes readings on the left and right side, as well as through the bale, for greater accuracy.

The 2178 mounts in the cab of the tractor and provides a direct readout for % moisture while baling hay.

Having multiple moisture content readings during each step of the haymaking process is critical to finishing with a high quality product.

FEATURES

- Bale type: Small square bales and round bales
- Large LCD display for easy viewing during day or night
- Average of readings updated and displayed every 2-3 seconds
- Illuminated keypad and text display
- \pm Moisture offset adjustments
- User can set the high and low limit of the moisture reading and will be alerted by a buzzer if exceeded
- Software upgradable via standard USB cable

Due to the many variables associated with hay moisture measurements an occasional "spot check" using a handheld probe on finished bales is recommended.



- Operating Range (Moisture): 8% to 40% depending on baler type used
- Accurate throughout the normal range of stored hay
- Display Resolution: 0.1% moisture